



# Product Data Sheet

## VIXOL TECHNICAL WHITE OIL (WOT)

VIXOL WOT Oils are severely refined hydro-cracked / hydro-treated oils with highest degree of purity and are stabilized with suitable additives for oxidation/UV stability. These oils are suitable for Industrial applications. The below oils are also recommended for Polystyrene and Thermoplastic industry.

VIXOL WOT Oils are offered in 200-250 liters' net HDPE / Steel Drums /IBC & in bulk Flexi bags or ISO tanks.

Test Description	Test Methods	Specification Limits								
		VIXOL WOP 60	VIXOL WOP 70	VIXOL WOP 80	VIXOL WOP 100	VIXOL WOP 150	VIXOL WOP 180	VIXOL WOP 250	VIXOL WOP 350	VIXOL WOP 500
Appearance	Visual ASTM	Transparent clear,colorless,odorless liquid freefrom suspended impurities								
Color, Say bolt	D156	+30								
Density @ 250 C gm/ml	ASTM D1298	>0.810	>0.820	>0.822	>0.820	>0.820	>0.835	>0.835	>0.850	>0.855
Kin. Viscosity @ 400 C, cSt	ASTM D445	7-11	11-14	14-17	18-23	27-33	30-35	36-45	68-72	80-85
Flash Point 0C min	ASTM D92	145	150	160	180	180	190	190	200	200
Pour Point 0C, max	ASTM D 97	-15	-15	-15	-12	-12	-12	-12	-12	-12

Vixol Australia Pty Ltd  
 7 Foden Avenue Campbellfield Vic 3061 Australia  
 Tel: +61 03 9333 7701 Local sales: 1300 084 965  
 Email: [sales@vixol.com.au](mailto:sales@vixol.com.au) [www.vixol.com.au](http://www.vixol.com.au)