



PRODUCT DATA SHEET

VIXOL WHITE - 100

White Oil Technical - Medium

VIXOL WHITE - 100 (TECHNICAL GRADE WHITE OIL) is a Medium white oil formulated from highly refined hydrotreated base oils which is colorless, tasteless and odorless.

APPLICATION

VIXOL WHITE - 100 is suitable for applications requiring a clear, colorless, and stable oil. It is commonly used in textile processing as a non-staining lubricant and in the manufacture of incense and perfumes. It also plays a key role in the plastic, paper, and rubber industries, where it functions as a processing aid and lubricant. In addition, it is widely utilized in oil-based formulations such as shoe polish, furniture polish, and protective coatings.

SR.NO	CHARACTERISTICS	UNIT	TEST METHOD	SPECIFICATION	
				MIN	MAX
1	Appearance	-	Visual	Transparent, colorless, bright and clear oily liquid.	
2	Color, Say bolt	-	ASTM D 156	+25	-
3	Density at 25°C	gm/ml	ASTM D 1298	0.810	0.860
4	Kinematic Viscosity at 40°C	cSt	ASTM D 445 / D 7042	18.00	24.00
5	Kinematic Viscosity at 100°C	cSt	ASTM D 445 / D 7042	Report	
6	Flash Point, (COC)	° C	ASTM D 92	170	-
7	Pour Point	° C	ASTM D 97	-	-12

PERFORMANCE BENEFITS

- Excellent oxidation resistance
- High film strength

Vixol Australia Pty Ltd
7 Foden Avenue Campbellfield Vic 3061 Australia
Tel: +61 03 9333 7701 Local sales: 1300 084 965
Email: sales@vixol.com.au www.vixol.com.au